

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number
WO 2005/068273 A1

(51) International Patent Classification⁷: **B62B 1/04**, 5/02, 5/04, B66F 3/00, 3/25, 9/08

(21) International Application Number:
PCT/AU2005/000028

(22) International Filing Date: 13 January 2005 (13.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004900194 16 January 2004 (16.01.2004) AU

(71) Applicant and

(72) Inventor: **WHITE, Anthony Renfrew** [AU/AU]; 28 King Street, Kingston, Queensland 4114 (AU).


(74) Agent: **CULLEN & CO**; Level 26, 239 George Street, Brisbane, Queensland 4000 (AU).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A HAND TRUCK



(57) Abstract: A hand truck (20) for transporting a load is disclosed. The hand truck (20) comprises a sub-frame (22) with a foot portion (47) extending therefrom so that the sub-frame is able to support the load, a main frame (21) engaged with the sub-frame (22) such that the sub-frame (22) is able to be extended and retracted with respect to a lower end (32) of the main frame (21), at least one wheel (62, 63) secured relative to the main frame (21) so that the truck 20 is able to be wheeled about, a motor (70), a controller (74) coupled to the motor (70) for enabling a user to control the operation of the motor (70), and a flexible linkage (77) coupling the motor (70), main frame (21) and sub-frame (22) together such that the motor (70) is operable to move the linkage (77) to thereby extend or retract the sub-frame (22).



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.